

**BW-i120-  
F28**



## **2MP IP Warm Light Bullet Camera**

Up to 1920 x 1080

S+265/H.265/H.264 Codec

Min. Illumination Color: 0.05 Lux,B/W: 0.01lux,0 Lux with IR

Smart IR, IR Range: 30m

Operating Conditions -35°C-60°C(IR OFF) / -30°C-40°C (IR ON), 0-95% RHG

PoE, IP67

With Audio

## DESCRIPTION

|                         |                                           |
|-------------------------|-------------------------------------------|
| Image Sensor            | 1/2.9" CMOS                               |
| Signal System           | PAL/NTSC                                  |
| Min. Illumination       | Color: 0.05Lux                            |
| Shutter                 | 1s to 1/100,000s                          |
| Lens                    | 3.6mm                                     |
| Lens Mount              | M12                                       |
| Day & Night             | IR Cut Filter with Auto Switch            |
| Wide Dynamic Range      | 100dB                                     |
| Digital Noise Reduction | 3D DNR                                    |
| Video Compression       | H.265/H.264                               |
| Video Bit Rate          | 32Kbps~8Mbps                              |
| Audio Compression       | Yes                                       |
| Audio Bit Rate          | Yes                                       |
| Network Storage         | Y                                         |
| NTP                     | Y                                         |
| ANR                     | Y                                         |
| Video Analytics         | Y                                         |
| EW                      | Y                                         |
| Alarm Trigger           | Motion Detection/IP Conflict/MAC Conflict |
| Protocols               | TCP/UDP/HTTP /DHCP/DNS /NTP /RTSP         |
| Remote Connection       | Y                                         |
| System Compatibility    | ONVIF (Profile S)                         |
| Audio Input             | Y                                         |
| Audio Output            | Y                                         |
| Communication Interface | 1-ch RJ45 10M / 100M Ethernet Interface   |
| Alarm Input             | Y                                         |
| Alarm Output            | Y                                         |
| Video Output            | Y                                         |
| On-Board Storage        | Y                                         |
| Operating Conditions    | -35°C~ 60°C, 0 - 95% RHG                  |
| Power Supply            | DC 12 V ± 25%, POE                        |
| Power Consumption       | MAX 7.5W (POE), MAX 6W (DC12V)            |
| Warm Light              | 4                                         |
| IR Distance             | 50m                                       |
| White Light             | Yes                                       |
| Impact Protection       | IP67                                      |
| Weight                  | 0.6KG                                     |



Call Us at  
**+91 8287958163**



**Sales@beware-essentials.com**  
**www.beware-essentials.com**



**MADE  
IN INDIA**